



## **Cleaning & Maintenance Guideline**

### **Exterior Rubber Tiles**

#### **A) Post Installation Cleaning**

- Remove dirt and debris left from installation by using a shop-vac.
- Tiles are coated with a water-based mold release residue, a natural result of the manufacturing process. This will initially cause slight discoloration and slipperiness.
  - For fast removal, clean with DinoClean or a neutral cleaner, agitate with brush or mop then rinse with water.
  - Exposure to sun and rain will naturally remove this residue, but the process may take up to four weeks.
- Keep moveable furnishings, planters, etc off newly installed surface for a minimum of 48-hours. This will allow tiles to be exposed to UV light and ensure even initial color adjustment.

#### **B) General Maintenance & Cleaning**

- Typically, Dinoflex NuVista® require less maintenance, routine cleaning and maintenance extends the life and enhances the appearance of the tiles.
- Sweeping and hosing off the surface are the most common methods of keeping the tiles clean.
- If the surface is excessively dirty, apply a solution of neutral cleaner and water and agitate with a brush. Rinse with a garden hose.
- Do not use a pressure washer to clean the tiles.
- Do not use solvents of any kind.

For additional information, please contact your Dinoflex Sales Representative, or for additional technical assistance, contact Dinoflex Recycled Rubber Innovators.

**Dinoflex Recycled Rubber Innovators**  
P.O Box 3309  
5590 – 46th Ave S.E.  
Salmon Arm, B.C. V1E 4S1 Canada

**Tel: (250) 832-7780**  
**Fax: (250) 832-7788**  
**Toll Free: 1-877-713-1899**  
**E-mail: [sales@dinoflex.com](mailto:sales@dinoflex.com)**

[www.dinoflex.com](http://www.dinoflex.com)

